



Leabourn & Rose Ltd

Heavy Machine Tools

Address: 87 Springs Rd, East Tamaki, Auckland

Email: info@leabourn-rose.co.nz Phone: (09) 274 6186

TECHNICAL DATA

Flection Modulus	80 cm ³
Minimum Outside Diameter	10 mm - 1/8" Gas
Maximum Shaft Speed	0-0.75 rpm
Maximum Center Line Radius (CLR)	700 mm
Minimum Center Line Radius (CLR)	36 mm
Power	3.5 kW
Voltage Requirement	Triphase 400V/ 50-60 Hz
Weight	400 Kgs
Dimensions (LxHxW)	850 x 850 x 1200 mm

TB 130
TOP BENDER®



MAXIMUM CAPACITY

Material	Max Ø (mm)	Max Thick. (mm)
Gas Tube	4" Gaz	8,56
Standard Steel Tube	127	7,1
Soft Brass	139,7	8,8
Stainless Steel AISI 308	114,3	5,6
Stainless Steel AISI 304	114,3	5,6
Welded Tube for furniture	127	7,1
Hydraulic tube ST35	100	11
Hard Copper and Aluminium	139,7	8,8
Round Solid	90	/
Rectangulare Solid	100 x 50	/
Rectangular Tube	120 x 60	9
Square Tube	90 x 90	10
Square Solid	75 x 75	/
Mild Steel T	1100 x 100	10
Mild Steel C	100 x 100	8