

Technical data		G3015F	G4020F	G6020F	G6025F
Working Area & Range	Working Area	3000mm × 1500mm	4000mm × 2000mm	6000mm × 2000mm	6000mm × 2500mm
	X axis	3050mm	4030mm	6030mm	6030mm
	Y axis	1525mm	2020mm	2020mm	2520mm
	Z axis	120mm	120mm	300mm	300mm
Accuracy	X/Y axis positioning accuracy	±0.03mm/m	±0.03mm/m	±0.03mm/m (Length overall 0.08 mm)	±0.03mm/m (Length overall 0.08 mm)
	X/Y axis repositioning accuracy	±0.02mm	±0.02mm	±0.02mm	±0.02mm
Max. speed	X/Y axis positioning speed	120m/min	120m/min	100m/min	100m/min
	X/Y axis linkage speed	169m/min	169m/min	140m/min	140m/min
	X/Y max acceleration	1.5G	1.2G	1.0G	1.0G
Weight & Dimensions	Max.weight work-piece	900kg	1600kg	2900kg	3600kg
	Weight	10000Kg	14000Kg	18000Kg	20000Kg
	Length x Width x Height [1]	9081mm × 2993mm × 2155mm	11230mm × 3470mm × 2320mm	14900mm × 3470mm × 2320mm	14900mm × 4020mm × 2320mm